



BEST PLUMBING SPECIALTIES

BEST NEW ITEMS

MAY 2023

KLEIN 7-IN-1 IMPACT DRIVER #11555

- #11559 7-in-1 5" flipsocket shaft only
- #99154564 3-in-1 3" flip socket shaft only
- #99154563 3-in-1 5" flip socket shaft only


This 7-in-1 Impact Flip Socket Set includes six integrated hex sizes plus a 1/4-Inch bit holding feature. It allows the user to change the shaft quickly and easily between a screwdriver handle and an impact driver and features color coding for easy identification.

FEATURES:

- Multi-function 1/4-Inch socket has both shallow (driver) and deep (bit holder) configurations for added versatility.
- Powerful Rare-Earth magnet securely holds bits and hex head fasteners.
- Features 1/4-Inch Quick-Connect adapter for easy use with an impact driver.
- Detachable sockets allow for easy removal of metal shavings from magnet.
- Sockets store on shaft in any order or orientation



6 INTEGRATED HEX SIZES



Scan QR Code for more info!

**All shafts fit in the 11555 Driver, 99921096 13-in-1 adjustable length driver, and the 11548 8-in-1 Adjustable Length Stubby Driver*

KLEIN DROP POINT KNIFE W/ DRIVER BIT #11560

This convenient tool from Klein is not just a knife, it's a stripper and driver too. It incorporates a No. 2 Phillips screwdriver, and a high-quality stainless steel full-sized drop point blade with three wire stripping notches on the back of the blade.



FEATURES:

- Full sized, fine edge drop point blade made of 440A stainless steel
- Pocket clip for easy storage
- 3 wire stripping notches. Sizes: 10 SLD/12 STR, 12 SLD/14 STR and 14 SLD/16 STR
- Rugged aluminum handle

CHEMLINK METALINK WHITE #61763

MetaLink is a multi-purpose neutral cure, silicone construction and roof sealant specially formulated for application in a variety of job site conditions. It is designed for use with many building materials including galvanized aluminum, metal, Kynar 500 PVDF coated metal, glass, and most roofing materials. MetaLink is isocyanate free and validated for ± 50% joint movement.



FEATURES:

- UV resistant
- Solvent-free, 100% solids will not shrink
- Non-slump, applies vertically and overhead
- 10-minute skin over

Ph: 800-448-6710
Fax: 800-700-2378



BESTGIVESBACK

For the month of April, Best donated to TheirWorld.



BEST FEATURED ITEMS

Did You Know Best Carries ...

Chemlink Clear

#61761



Clear is a general purpose, high performance, moisture cure sealant that can be used to seal a wide range of construction materials. Clear forms a transparent, elastic, waterproof seal to most metal, anodized aluminum, glass, vinyl, wood, masonry, polystyrene, and many engineered plastics. Clear bonds to most siding, window, metal flashing, and HVAC and can serve as a clear roof sealant as well. **pg. 6-71**

- Solvent free, 100% solids will not shrink.
- Non-slump, applies vertically and overhead.
- 20-minute skin over
- No outgassing on damp surfaces
- Paintable after 24 hours

Diablo 5-PC Universal General Purpose Oscillating Blade Set

#99802310



This 5-piece set contains high performance carbide and bi-metal blades for greater durability, life, and quality of cut. Each blade is universal fit and works in most multi-tool brands like Bosch, Craftsman, Dewalt, Milwaukee, Ridgid, and more.

Includes:

- #99778905 1-1/4" Bi-Metal for Nail-Embedded Wood
- #99778898 1-1/4" Carbide for Metal
- #99778899 1-1/4" Carbide for General Purpose Cuts
- #99778906 1-1/4" Bi-Metal for Clean Wood
- #99778907 2" Bi-Metal for Drywall

ADA Full Tubular Cover Kit #80018



Scan QR code for more options

These ADA-Compliant covers are made of flexible EVA foam to easily fit different systems and reduce risk and liability. Simply cut to size and press the Velcro together for a durable hold. The UV resistant foam won't yellow over time and is anti-bacterial, anti-fungal, and anti-microbial. **pg. 8-4**

Torx Partition Bolt Kit #99152683



Contains a 9-piece bit set alongside an assortment of 175 button head, torx pinhead, and shoulder screws as well as barrel nuts for all your partition repairs. **pg. 2-4**

Chicago Emergency Thermostatic Mixing Valve with Cold Water Bypass

#99931005



This valve features a cold water bypass that allows exceedingly hot water temperatures to pass through the line in an effort to purge bacteria and viruses. Perfect for VA hospitals.

- Inlet: 3/4" NPT inlet
- Outlet: 1" NPT outlet
- Maximum operating pressure: 125 PSI
- Outlet temperature range: 60°F-95°F (15°C-35°C)
- Maximum hot water supply temperature: 180°F (82°C)
- Flow Rate: 1.0 – 35.1 GPM @ 30 PSID

WE CARRY **WATTS**



BACKFLOW PREVENTION ASSEMBLY KITS